

mDECK Solid io




Overview

Take your content production to the next level with mDECK Solid io, a professional media deck that ensures incredible reliability and elasticity with the combination of record, ingest, transcode, and playback operations in UHD, FHD, and NDI. All in a single box.

This powerful appliance ensures broadcast quality for hybrid workflows (file-based and live) while supporting the most used formats on the market.

Additionally, it has an option for local storage of 8TB, PSU redundancy, and an OS Drive.



Highlights

- Live to live - multiple simultaneous records
- Batch capture
- Closed captions
- Multiple simultaneous transcodes
- File playback - multiple simultaneous plays
- Metadata preservation, enhancement, and enrichment
- Playlist management
- Media checksum
- Quality control, audio, and video report
- Flexible file naming and renaming engine
- Locators support
- Automated file ingest
- Supports spanned clips
- Proxy generation
- Playout preparation and control
- Improved security
- Artificial intelligence

Specially Designed For

- Educational/Government
- Live Entertainment/Worship
- Corporate
- Sports
- Film/TV Studio/Scripted
- Digital News
- Digitalization
- Archiving
- Post-Production
- Broadcast/Digital News
- OTT & Streaming
- System Integrators/Rentals

Features

Features
Timecode support
LTC (SMPTE 12M)
VITC (SMPTE RP188)
Time of Day
Serial Control Protocols
VTR (BVW) - Serial
VTR (VDCP) - Serial
Multiple LIVE and simultaneous records
Crash Record operations
Gang Capture operations
Independent workflow selection in Gang Captures
Unique workflow for gang captures while using clipnaming with counters
Conceal/Hide option for unused Capture Instances
Synchronize (different) Gang Captures
Flexible Gang Capture channel configurations / Choose which channels are present in the gang
Frame Chase editing
Unlimited capture duration support
Growing files support
Growing file support for Grass valley Edius Workgroup v.9 and X
Growing XDCAM MXF OP1a file support on Avid Media Composer *required Nablet AMA Plugin
Automatic Stream Control - Detect input streams and start recording automatically
Continuous recording support
Continuous live stream capture
Recording timer for captures
Abort or force stop a capture or a stream
Frame rate conversion option on Capture workflows
Generate MP4 files as Fragmented MP4 via DCP Packager
Add XML sidecars with WAV file as output while recording
Perform "Run after completion" scripts
Remove source assets after Job completion for all plain sources
Live Probing option
Stream with Closed Captions
Edit a Workflow directly from the Player
Input selection made directly from a dropdown list on the player
Option to start timecode recording from 00:00:00:00
Export in "MOG playlist" format (.XML Sidecar containing information about the chunks of the recorded media)
Batch record support
Deck control through Serial Ports
Pre-roll and post-roll options
LiveU NewsML batch capture
LiveU NewsML metadata import
LiveU NewsML - support XML from devices (Live U, Android and iPhone)
LiveU include subfolder browse
Contribution Web Video Player - Aspect marker, Safe Area Marker, and Center marker
Player Overlay - Center Dot and Cross
Support for Active Format Description (AFD)
Medialoopster Integration in Capture operations
Medialoopster Integration in Batch Capture operations
Measurement of consumption (Number of bytes for input/output "lives")
Video Router Protocols
Quartz
Probel SW-P-08
Jupiter ASCII
Blackmagic Videohub Ethernet Protocol
Operation modes
Automatic
Manual
Scheduled

Features

Clipnaming

- Flexible file renaming engine
- Create diversified clipnaming templates
- Clipnaming based on Metadata Profiles
- Use of common labels (Id, label, Counter, Date, Original Source Name, Weekday, User)
- Field numeric representation of the day of the week
- Folder Structure creation
- Drag and Drop support
- Restore auto numbering on capture abort in naming templates
- "CreationDate" field can refer to a desired Time Zone
- Add the label "_p" to proxy clips' names

Multi-Configuration metadata management and enrichment

- An efficient internal asset management
- Quickly search for assets metadata
- Directly manage your assets metadata
- Generate metadata directly through capture operations
- Prevent the overwrite of metadata fields
- Protect metadata fields
- Reset metadata fields
- Delete custom metadata
- Edit group clips metadata
- Edit a file's source metadata based on a configured metadata profile
- "Description" field editable in metadata widget
- Set "Description" field as a column in the Asset Explorer list view
- Forward metadata to Gang Captures
- Favorite metadata fields
- Create custom metadata fields
- Add a "Rating" metadata field
- Update the source metadata directly through the metadata widget
- Add asset tags insertion in preset list
- Re-use lists of possible values
- Update Metadata in Media Central/Interplay using AMT-3 library
- Rename media in Interplay after a capture has begun
- Take field (counter)
- Support for "Reel" metadata field using Apple ProRes Wrapper
- Read metadata from pre-configured cloud storages (Amazon S3 / Google Cloud Storage / Tencent / IBM Cloud Object Storage)
- Preserve specific Arri fields
- Preserve RED digital cinema color information

Find immediately and learn everything about any asset

- Show or hide proxies on Asset Browser
- Sort, order and search for files on Asset Browser
- Asset Explorer - Resizable thumbnails
- Asset Explorer - Support asset availability
- Search for all assets on Asset Explorer
- Extract thumbnails and posters while indexing on Asset Explorer
- Asset Explorer - Playable thumbnails
- Preview media with interactive Pop-up Players
- Asset Explorer - View the exact duration of files with more than 24 hours
- Asset Selection -View the total duration of the selected assets
- Configure the asset's preview duration
- Asset Selection - Add Numeric Input

Asset management Check-in

- AVID AAF
- AVID interplay
- XML support
- XSLT transformation - XML sidecar
- Edit share flow
- Vizzi OTT check in
- Support for update on Vizzi OTT check-in

Features

Audio support

- PCM input and output support
- Dolby E-AC-3, Dolby TrueHD, and DTS input support
- Dolby-E Input and output support
- DTS Coherent Acoustics (DCA)
- Integration with Dante Audio Capture *Negotiated separately
- PCM 96KHz support
- Independent audio encoder for hires and proxy
- Individually map your audio by output target
- Record audio only streams
- Playout audio only streams
- Loudness normalization (EBU R128)
- Audio downmixing & upmixing
- External audio files support (.WAV)
- MPEG-4 Audio (M4A) audio format as output
- Ability to mute proxy on the output

Close captions

- CEA/EIA - 608
- Scenarist (SCC)
- Add sidecar - SubRip (SRT)
- Add sidecar - Fragmented WebVTT
- Add sidecar - ISMT/CMFT subtitles
- DCP subtitle burn-in (.SCC)
- Digital Cinema Package (DCP) open captioning
- Support DVB-S captions in streams
- Support captioning for OTT (CMFT, SubRip, and WebVTT)
- Stream with Closed Captions

Locators

- Create locators with shortcut keys
- Edit and delete locators
- Edit the locators' description
- Insertion and viewing
- Create and freely customize action fields
- Insert comments in a marker's widget tab
- Locators source in markers widget
- Select multiple subcategories for a single locator
- Order asset locators by timecode
- Establish Absolute or Relative timecode for source locators
- Enter Timecode without the need of entering colons
- Eject locators using the player eject button
- Merge locators
- Support for locators with AMT captures
- Send locators directly to Gang Captures
- Send locators instantly to Playout
- Preserve Metadata Enhancement locators created by an Automatic Job

Scheduler (Calendar View)

- Schedule a Record operation
- Schedule Automatic Jobs
- Schedule Gang Captures
- Schedule Playouts
- Schedule Maintenance Tasks (Reboot, Export Logs, Export Full Backup)
- Edit individual events
- Export activity events
- Allow editing of settings for each occurrence/repetition
- Set the number of an event's repetitions
- Check for collisions between events and repetitions
- Ability to Ignore files before a start date
- Placeholder when editing an occurrence name
- Enable field event name as AVID Interplay clipname by default
- Use pre-set naming templates
- Send the assets to independent targets and multiple outputs

Features

- Establish a maximum capture duration
- Configurable number of iterations when using maximum capture duration
- Use AVID Interplay clip name as event name on crash record events
- Pre-roll and post-roll options for scheduled events
- Define events to be triggered on any day, on working days only or only on weekends
- Set the Calendar Notion option to automatically adjust to daylight time
- Edit the Start Time field after the first recording
- Visualize scheduled events in a List View
- Perform captures from an Airspeed 5000

Scheduler (Record Grid) - Unifies in a single rollout view all ingest activities *Optional

- Schedule a Record operation
- Schedule Gang Captures
- Create new scheduled events directly from the timeline
- Perform crash record captures directly from the grid view
- Metadata Insertion availability
- Use of pre-set naming templates
- Edit scheduler individual events
- Edit an event after it has started
- Edit settings for each occurrence/repetition
- Trigger Capture events (Any day, On Working Days or only on Weekends)
- Adjust events by dragging them on the timeline
- Check collision between events with repetitions
- On channel settings assign an Input a workflow a router source and a duration and start recording on the fly
- Change router source cross point from record scheduler during a live event
- Change router source on rollout
- Copy an event's name after it is complete
- Perform captures from an Airspeed 5000
- Pre-roll and post-roll options for scheduled events
- Configure the number of events repetitions
- Define events to be triggered on any day, working days or weekends only
- Set the Calendar Notion option to automatically adjust to daylight time
- Expandable and collapsible views
- Jump to date to seek events by day or in a 7 days period
- Choose between AVID or MOG color schemes
- Confirm a "Stop" action

Scheduler (Playout Grid View) - Unifies in a single rollout view all Playout activities *Optional

- Grid View for Playout
- Crash Playout directly from the Grid View
- Loop a playlist
- Schedule Clip Lists to be Played out
- Adjust to a desired Time Zone
- Ability to set a pre-determined number of repetitions
- Trigger Playout events (Any day, On Working Days or only on Weekends)

Router Control *Optional

- Support for Black Magic Video Router
- Support for Grass Valley Sirius Video Router
- Support for Evertz Quartz Video Router
- Support for Jupiter ASCII
- Change router points directly on the player
- Capacity to setup the number of sources and destinations
- Option to choose to make use or not of a source
- Assign a mnemonic to each source
- Ability to provide an alternative name to a router mnemonic
- Assign in the crosspoint tab a source to each router destination
- Lock sources to each router destination
- Configurable connection through IP or host name to the destination router

Signal error detection and related recovery actions

- Detect possible signal errors
- Detect possible drop frames
- Support for timecode breaks
- Configurable capture resume methodology

Features

Automatic streaming (headless) - Restart capture after stopping/crashing or rebooting

Checksum media

MD5 hash file

MDL - Media hash list

Live to Live

Delete artifacts on abort

Vizzi OTT Live Output

Multiple resolutions check-in

Support Time of Day in input streams (RTMP, MPEG-TS, RTP, SRT, RTSP, HLS, LLDASH, MSS, MPEG-DASH, CMAF)

Support Live Stream from sCapture as rPayout input

Variable Frame Rate Input

Support IGMPv3 multicast

Add possibility to change the transport stream segments duration

MPEG-TS Support

Capture of MPEG-Transport Streams

Support of MPEG-TS program IDs

NDI

Native NDI output

NDI HX Support

NDI audio and video synchronized mechanism

NDI discovery mechanism

Capture multiple NDI sources

Time of day and embedded timecode options in NDI input

HLS

Configurable HLS segment duration

Configurable HLS Playlist segment count

RTMP

RTMP recording with absolute timecode

RTMP Push Mode in input and output

RTMP Pull Mode in input and output

Native RTMP listener capability

Multiple audio channels in RTMP Output

HEVC, VP9 and AV1 codec in enhanced RTMP/FLV

SRT

Input modes: Caller, Listener, and Rendezvous

SRT listener mode as stream output

Output modes: Caller and Rendezvous

Stream ID support

Configurable latency settings

Configurable overhead bandwidth

Configurable passphrase

Monitoring input metrics

WebRTC

h.264 Support

VP8 Support

VP9 Support

File ingest

Execute multiple simultaneous transcodes

Batch ingest

Card ingest

Clip merge

Clip renaming

Disable Clip File Naming generation

Partially restore clips

Rough cut

Establish priority levels

Pause File Based ingest operations

Insert Subclips SOM and EOM without colons

Automatic drag and drop ingest

Drag and drop media from several social networks

Generate XML sidecar with WAV file as output while ingest

Features

- Generate a .xml file for each output AVID clip or AVID sequence
- Ingest Apple ProRes wrapped in OP-Atom to Avid
- Support of Avid OP-Atom files with Apple ProRes essence
- Merge as Sequence from MP4 proxy files
- Merge as sequence by sequence XML for MP4
- Automatically select workflows available in job control attending the source files
- Cut growing files and send them to (a playlist for) playout
- Directly select the storage on the dashboard instead of accessing workflow profiles
- Copy assets
- Group resulting assets into a single one
- Copy - Transfer sidecars if available
- Encode the contents according to the destination format
- Decode the contents according to the destination format
- Move assets
- Edit while transcoding/ingesting
- Place locators on growing files
- Multiple resolutions check-in
- Frame rate conversion
- Variable Frame Rate Input
- High Dynamic Range (HDR) support - HLG (arib std-b67) / PQ (SMPTE 2084)
- High Frame Rate (HFR) up to 120fps (ST2081-10, ST2081-11, ST2082-10, ST2082-11 and ST2082-30)
- Ability to perform "Run after completion" scripts
- Audio only OPAtom as output
- Opt to not overwrite files
- Support for .MOV files containing "Run-length encoding" video essence
- Enable "growing" support on EDL ingest workflow
- Timecode SUM of selected cuts
- Merge assets as EDL, regardless of the input's format
- Merge Trimmed files
- Merge files with different framerates
- Merge P2 with different audio channels
- Merge operations for Devices sources
- Allow the merge of more than 200 assets
- Support for spanned Panasonic P2 structure
- Preserve original time code breaks in Panasonic P2 Format
- Mute proxy option in output (requires proxy option)
- Create Edit Decision Lists with cut points
- View the total duration of the sub-clips in an EDL widget
- Ingest from cloud locations
- Digital Cinema Package (DCP) support
- Choose to force fragment MP4 clips while uploading to a S3 bucket
- Generation of MP4 files as fragmented MP4 with DCP packager
- Digital Picture Exchange (DPX) support
- Select IMF (Netflix Compliant) as the output metadata
- FTP for generic network devices as input
- Ability to delete OPAtom source files after ingest
- Support for GOPRO spanned files
- Support video with vertical rotation
- MOG file package support
- Support MOG Package from Cloud Storages
- Outgest growing media directly from Interplay
- Dual check in to interplay in a merge as sequence operation with the same MOBID for the sequences
- HDR (PQ, HLG) conversion to SDR as output
- Ingest image files
- Support 48fps drop frame media (DJI Camera Drones)
- Support for spanned clips
- XDCAM support for spanned & merge clips in network locations/network devices
- Delete an Output via Job Abort
- Schedule an Ingest operation through the Calendar via Automatic Jobs
- Ingest and/or transcode the contents according to the destination format
- Vubiquity assets support

Features

- Support for Vizzi collections as input files
- Browse Avid Interplay folder structure from within the "Workflow selection window"
- Avid Sub Clip export referencing Growing Master Clip
- Generate Avid OPAtom assets to an FTP server
- Update Metadata in Media Central/Interplay using AMT-3 library
- Create Live Ingest Operations
- Live Sources made available in the Asset Browser/Explorer widgets
- Override start timecode
- Index clips with same name but with different metadata
- Exclude file extensions from File inputs
- Measurement of consumption (Number of bytes for input/output "files")

Burn-In Video options

- Graphic burn-in while recording
- Graphic burn-in while ingesting
- Text (Position, Text color, Box Color, Font Size)
- Timecode (Position, Text color, Box Color, Font Size)
- Overlays support (images and videos positioning)
- LUT (Look-Up Table) - Save particular color grades as a template

Automated ingest

- Create Automatic Jobs
- Dynamic workflows using metadata fields
- Dynamic workflows with support for metadata without sidecars
- Delete Assets in Dynamic Jobs
- Support different input types on dynamic configurations
- Ignore files before a start date
- Re-process assets with the same name
- Support metadata enhancement workflows
- Vizzi Collections support

File playback

- Simultaneous playback
- Composition play
- Instant play
- Gang Play
- Replay a group or an individual asset
- Loop playback
- Group Loop Playback
- Gridline (3x5) Overlay
- Remote preview
- Support for 10bit
- Synchronous SDI playback of multiple files
- Closed captions
- Cue mode
- Monitor - support HDR
- Option to add locators
- Play assets from cloud storages
- Preview Editing Decision Lists
- Preview Clip Lists
- Playback - 8K UHD
- Embedded VITC output support
- Step multiple frames forward and backwards on SDI/gang playback
- Timecode and metadata overlaying on SDI out
- Support for growing assets in player
- Support for spanned assets in player
- Timecode only monitoring
- Use of a contour shuttle to control an asset during playback
- Playback duration showing the remaining time of the clip
- Remove clips
- Reorder clips
- Export playlist
- Create new playlists with the current assets selection
- High Dynamic Range (HDR) support - HLG (arib std-b67) / PQ (SMPTE 2084)

Features

- High Frame Rate (HFR) up to 120fps (ST2081-10, ST2081-11, ST2082-10, ST2082-11 and ST2082-30)
- Preview - Possibility to change the playback speed by multiplier factors
- Simple Time Delay: Scheduling a Playback of a Single File in Growing Recording Mode
- Read Metadata Timecode Package (Auto / Material Package / Source Package)

Playout

Playout Preparation

- Build playlists in a Playlist Builder widget
- Create multiple Playlists
- Allow configuring playout clip action while preparing the playlist
- Support visual separators for rPlayout playlists
- Drag and Drop clips to the player for media preparation
- Support insertion of Timecodes without separators ":" in the playlist builder
- Use both types of TC (Relative and Absolute) for Mark-ins and mark-out at playlist builder
- Trim clips to be included in the Playlist
- Editable timecodes of the in and out points
- Re-arrange clips order
- Duplicate Edit Decision Lists
- Export Edit Decision Lists

Playout Control

- Edit playlist on the fly and while playing
- Playlist countdown and clip countdown
- File and clip list progress bars
- Playout Capture streams through SDI and native window
- Print to tape
- Queue clip on the playlist
- Queue on first frame and last frame
- Queue on first frame the first clip of the playlist
- Bypass action for playout clips
- Pause Playlist
- Playout to stream
- Thumbnail preview of the current clip on the playlist and its remaining time until Playout of the next clip
- On Air - current loaded playlist name
- Loop a playlist
- Loop one or more assets in the playlist
- Drag and Drop Clip List entries in Playout Control
- Multi-channel playout capability
- Schedule Playout
- Choose between Playout Services available - rPlayerSDI or CasparCG
- Mini control bar for use with Playout Control
- Keyboard shortcuts for playout control and associated WEB player
- Autoplay option
- As Run Log's containing Date, Time, Clip name, Time Code In, and Time Code Out
- Prepare the Playout clip actions while preparing the playlist
- Seamless playback without black frames when "jump to" in a playlist

Input/output social media *Optional

- Capture to Facebook Live
- Stream to Facebook Live
- Stream to Twitch Live
- Capture to YouTube Live
- File based YouTube Upload
- Capture X (Twitter) Live
- Stream to X (Twitter) Live
- Upload to Vimeo
- Metadata social annotation and enhancement

PAM - Production Asset Management *Optional

- Advanced text search
- Asset browser permissions
- Asset collections
- Asset essences
- Asset essences for generic sources
- Asset comments

Features

- Enable on-the-fly tagging
- Flexible metadata management
- Dynamic Automatic Jobs - Age value for CreationDate (Available for Copy, Move, Archive Workflows)
- Display of Essences File Paths
- Check-in via detector
- Check-in via metadata update
- Check-in via workflow
- Interactive approval workflows
- MOG player proxy
- Optional Proxy creation
- Manual Proxy creation
- Move option in asset collections
- Collections as input in automatic jobs
- Private and shared asset collections
- Show the creator of the collection
- Statistics for collections
- Save searches and filters
- Rich logging workflows
- User abstraction for in/out assets
- Instant play, anytime and anywhere of any asset (with or without proxy)
- Disk-to-Disk Storage Manager (Archive and Restore)

Metadata Enhancement and preservation

Artificial Intelligence

Audio

- Audio clipping detection
- Loudness detection
- Silence detection
- Voice activity detection
- Audio mute detection
- Audio phase detection
- Mono audio detection

Video

- Black frames detection
- Video freeze detection
- Scene change detection
- Black Margins detection
- Flashing video detection

Object

- Concept tagger 2.0
- Vehicle detection
- License plate detection

Others

- Timecode gap detection
- Update existing interplay entry with new metadata
- Possibility to add bounding boxes to player

Transform

- Automatically Blur License Plates
- Black margins automatic crop
- Remove audio clicks
- Remove audio clipping
- AI Upscale
- Reduce video flashing

Additional AI Operations *Optional

- Face recognition 2.0
- Face recognition - Support dataset with multiple images for each person
- Object detection 2.0
- Optical Character Recognition (OCR)
- Speech recognition 2.0 (with ability to detect non speech tokens)

Analytics

- Integrate with Google Analytics and Tag Manager
- Enable or disable Analytics

Features

Keep track of menu events

Receive video metrics

Keep track of Job Control widget's events

Keep track of Asset Explorer widget's events

Improved security

Support for Windows UAC

Support for HTTP/HTTPS Ingress

HTTPS (Hypertext Transfer Protocol Secure) for REST API

Secure login

User Impersonation

Token based authentication

Two-factor authentication

Remote services, system restart, and settings recovery features

Database replication

Opt to "Keep me signed in"

Send a User Verification through email

Configurable password visibility in logs

Orchestration

Orchestration View for output workflows

Services Menu that eases Group and Cluster Configuration while displaying running services per node

Transfer acceleration protocols

Aspera FASP transport technology - Transfer acceleration protocol

FileCatalyst direct - Transfer acceleration protocol

Hardware acceleration *If Hardware is installed or available

Nvidia Nvenc

General Purpose IN/OUT

GPI triggers supported

GPO triggers supported

Additional Highlights

REST API - allows interaction with RESTful web services

Change Aspect Ratio (4:3 / 16:9 / 1.9:1 / 2:1 or use same as source)

Active Format Description (Option to Preserve, Discard or Override)

Protection against overwriting files

Notify user upon connection lost with the Server

Manage via web interface or REST APIs for integration with automation system

Configurable quality and target latency of the preview stream

Logging - Human readable information on Services logs

Logging - Add user information on flow actions

Logging - Structured Logging

Receive SMTP notifications via e-mail

Support an external Database

Microsoft Edge / Firefox / Safari and Chrome Support

Unified Interface User Experience

Unified GUI for all services and group of servers in the farm

Configurable web interface access port

Embeddable Dashboards/Widgets

Environment Dashboard which enables an overview of group servers in workgroups

Web-Based Interface with video preview

Dashboards based experience where users can create their own personalized view

Dashboards presets for ease-of-use deployment

Create your own custom dashboard templates

Import and Export Users' Dashboards

Associate a single dashboard to multiple users

LDAP user authentication

User profile management

Users permissions control

Widget based modular interface

Lock/Unlock widgets permission

Choose between multiple interface themes (Midnight, Carbon, Dark or High contrast theme)

Touch screen mode

Monitoring - Advanced metrics

Features

Multi Language Support
User tour
Show/Hide player overlays
Notifications of required actions needed to resume a workflow
Monitor Grouped Servers' activity in a Group Activity Widget
Remove the "quick edit" button from the Job Control Widget
(Set Permissions to) Activate or Deactivate Settings of a Gang Capture widget
Multiviewer
Define the quality and target latency of the preview stream
Ability to control to up to 8 players in a single dashboard
Ability to control to up to 4 players in a single dashboard
Maintenance
Scheduler
Reboot host or group
Export database (backup) as a scheduled task
Export logs as a scheduled task
Activity
Export last activity
Export all activity
Export activity from a date range
Clear all activity
Logs
Export logs
Backup
Export full backup - A full backup will create an archive of all the files and configurations
Import full backup
Dashboards
Export dashboards from one user or all users
Import dashboards
Data
Clean data usage
Clean assets, flows and notifications
Perform a Factory Data Reset
Erase all data and reset the system
Force clear cache

Technical Specifications

Supported File Inputs

Inputs

OnPrem	Plain Files or Structures
	ARRI ALEXA Cameras
	BlackMagic Cameras
	RED Digital Cinema
	Avid Files
	Avid Media Files (standalone or Nexis)
	Avid Sequences (master clips and rendered sequences)
	CANON DSLR 5D, 7D, C300, C100
	GoPro Cards
	IKEGAMI GFPAK
	JVC (AVC HD models)
	NextoDI NSB-25
	Panasonic AU-EVA1 and GH5 Cameras
	Panasonic P2
	AJ-PCD 2 / AJ-PCD 20/30/35 / AJ-MPD1
	AU-XP1E / AU-XP3EJ
	XDCAM EX
	Sony SxS (SBAC-UT100, SBAC-US10/20/30)

Inputs

OnPrem	XDCAM HD
	Sony XDCAM HD: Disc (PDW-U1, PDW-U2, PDW-U4)
	XAVC Structures
	DJI (Camera Drones)
	HLS Structures
	MPEG-TS Structures
	MOG Package
	Network
	XDCAM Network
	P2 Network
	ARRI RAW Network
	Ikegami Network
	Storage
	Avid Nexis
	Avid Unity™ MediaNetwork
	DDP – Dynamic Drive Pool
	Facilis TerraBlock
	Harmonic MediaGrid
	Editshare EFS
	NAS / SAS (SMB 2.0 and 3.0)
Quantum StorNext	
ScaleLogic NX2 & ZX NAS Storage	
EMC Isilon	
QNAP	
Studio Network Solutions EVO	
Oracle Storage	
Netapp	
Cloud	Social Media
	Facebook
	X (Twitter)
	Vimeo
	YouTube
	Professional Cloud Storages
	Adobe Creative Cloud
	Amazon S3 Glacier
	Microsoft Azure Storage
	Tencent
	Lucidlink Cloud NAS
	Google Cloud Storage
	IBM Cloud Object Storage
	Generic S3 storages
	Consumer Cloud Storages
	Apple I Cloud Drive
	Dropbox
Google Drive	
Microsoft One Drive	

Supported File Outputs

Outputs	
OnPrem	Avid Nexis
	Avid Unity™ MediaNetwork
	DDP – Dynamic Drive Pool
	Facilis TerraBlock
	Harmonic MediaGrid
	Editshare EFS
	NAS / SAS (SMB 2.0 and 3.0)
	Quantum StorNext
	ScaleLogic NX2 & ZX NAS Storage
	EMC Isilon
	QNAP
	Studio Network Solutions EVO
	Oracle Storage
	Netapp
	FTP Servers (List on request)
Generic File Shares	
Cloud	Consumer Cloud Storages
	Apple I Cloud Drive
	Dropbox
	Google Drive
	Microsoft One Drive
	Multiple and Adaptive bitrates for the OTT *Optional
	Professional Cloud Storages
	Adobe Creative Cloud
	Amazon S3 Glacier
	Microsoft Azure Storage
	Tencent
	Lucidlink Cloud NAS
	Google Cloud Storage
	IBM Cloud Object Storage
	Generic S3 storages
	Social Media *Optional
	Facebook
	X (Twitter)
	Vimeo
	YouTube

Supported Live Inputs

Inputs	
Live	SDI
	SD-SDI (SMPTE 259M)
	3G-SDI (SMPTE 292M, SMPTE296M, SMPTE372M, SMPTE425M)
	12G-SDI (SMPTE ST-2081/SMPTE ST-2082, SMPTE/2108-1)
	12G-SDI (Quad-Link 3G-SDI)
	Support for 8, 10, and 12 bits
	Streams
	Video Content Hyperlinks
	HLS
	MPEG-TS
	MPEG-DASH
	RTMP (with support for HEVC / VP9 / AV1)
	RTP
	RTSP
	NewTek NDI
	UDP
	Haivision SRT
	WebRTC
	Zixi

Inputs

Live	Audio
	Dante audio *Negotiated separately
	Social Media
	Facebook
	Twitch
	X (Twitter)
	YouTube

Supported Live Outputs

Outputs

Live	SDI
	SD-SDI (SMPTE 259M)
	3G-SDI (SMPTE 292M, SMPTE296M, SMPTE372M, SMPTE425M)
	12G-SDI (SMPTE ST-2081/SMPTE ST-2082, SMPTE/2108-1)
	12G-SDI (Quad-Link 3G-SDI)
	Support for 8, 10, and 12 bits
	Streams
	HLS
	HTTPS Push
	Microsoft Smooth Streaming
	MPEG-DASH
	Low Latency Dash - LL-Dash
	NewTek NDI
	MPEG-TS
	RTMP (with support for HEVC / VP9 / AV1)
	RTP
	RTSP
	UDP
	Haivision SRT
	WebRTC
	Vizzi
	Live Output
	Social Media *Optional
	Facebook
	Twitch
	X (Twitter)
	Vimeo
	YouTube
Multiple and Adaptive bitrates for the OTT *Optional	

Formats

Input Formats

Input Video Formats

ARRI ARRIRAW
Blackmagic RAW
Digital Cinema Packages (DCP)
Digital Picture Exchange (DPX)
RED Digital Cinema
IMX 30/40/50 Mbps
MPEG2 LGOP 18/25/35 Mbps 4:2:0
MPEG2 LGOP 50/70 Mbps 4:2:2
MPEG2 LGOP 422 50 Mbps
MPEG2 LGOP 420 1440x1080 35 Mbps
MPEG2 LGOP 420 (FULL) 35 Mbps
DVCAM 25 Mbps
XAVC Intra 50 / 100 Mbps
XAVC LGOP 25 / 35 / 50 Mbps
DVCPRO 25/50 Mbps / DVCPRO HD 100 Mbps
AVC-Intra 50/100 Mbps

Input Video Formats

AVC-Intra 200 Mbps
AVC-Intra 2K422
AVC-Intra 4K422
AVC Ultra (LGOP 6/12/25/50 Mbps)
DNxHD (SQ/HQ/HQX/LB)
DNxHR (SQ/HQ/HQX/LB)
H.264 4320P 80 - 150 Mbps High Profile
H.264 4320P 150 - 280 Mbps High Profile
H.264 2160p 35 - 68 Mbps High Profile
H.264 1440p 16 - 24 Mbps High Profile
H.264 1080p 8 - 12 Mbps High Profile
H.264 720p 5 - 7.5 Mbps High Profile
H.264 480p 2.5 - 4 Mbps High Profile
H.264 360p 1 - 1.5 Mbps High Profile
H.264 2160p 13 - 51 Mbps High Profile (Live)
H.264 1440p 6 - 18 Mbps High Profile (Live)
H.264 1080p 3 - 9 Mbps High Profile (Live)
H.264 720p 1.5 - 6 Mbps High Profile (Live)
H.264 480p 0.5 - 2.0 Mbps High Profile (Live)
H.264 360p 0.4 - 1.0 Mbps High Profile (Live)
H.264 240p 0.3 - 0.7 Mbps High Profile (Live)
H.264 L10 10 Mbps
H.264 MOG 1Mbps
H.265/HEVC 10 Mbps LGOP
H.265/HEVC 25 Mbps LGOP
H.265/HEVC 50 Mbps LGOP
H.265/HEVC 100 Mbps LGOP
H.265/HEVC 4K 25 Mbps LGOP
H.265/HEVC 4K 50 Mbps LGOP
H.265/HEVC 4:2:2 LGOP
H.265/HEVC 4K 4:2:2 LGOP
NDI HX H.264 - High Profile
NDI HX H.265 - High Profile
MPEG-5 EVC Baseline Profile
MPEG-5 EVC Main Profile
MPEG VVC/H266 Main Profile
ProRes 422 (SQ/HQ/LT)
ProRes 4444
ProRes 4444XQ
Google® VP6 / VP7 / VP8 / VP9 (Full HD)
Uncompressed UYVY 422 / V210 / RGBA
AOMedia Video 1 (Full HD)
AOMedia Video 1 (4K)

Output Formats

Output Video Formats

IMX 30/40/50 Mbps
MPEG2 LGOP 18/25/35 Mbps 4:2:0
MPEG2 LGOP 50/70 Mbps 4:2:2
MPEG2 LGOP 422 50 Mbps
MPEG2 LGOP 420 1440x1080 35 Mbps
MPEG2 LGOP 420 (FULL) 35 Mbps
DVCAM 25 Mbps
XAVC Intra 50 / 100 Mbps
XAVC LGOP 25 / 35 / 50 Mbps
DVCPRO 25/50 Mbps / DVCPRO HD 100 Mbps
AVC-Intra 50/100 Mbps
AVC-Intra 200 Mbps
AVC-Intra 2K422
AVC-Intra 4K422
AVC Ultra (LGOP 6/12/25/50 Mbps)

Output Video Formats

DNxHD (SQ/HQ/HQX/LB)
DNxHR (SQ/HQ/HQX/LB)
H.264 4320p 150 - 280 Mbps High Profile
H.264 4320p 80 - 150 Mbps High Profile
H.264 2160p 35 - 68 Mbps High Profile
H.264 1440p 16 - 24 Mbps High Profile
H.264 1080i 35 Mbps High Profile
H.264 1080p 8 - 12 Mbps High Profile
H.264 720p CBR - 6.5 Mbps High Profile
H.264 720p 5 - 7.5 Mbps High Profile
H.264 480p 2.5 - 4 Mbps High Profile
H.264 360p 1 - 1.5 Mbps High Profile
H.264 2160p 13 - 51 Mbps High Profile (Live)
H.264 1440p 6 - 18 Mbps High Profile (Live)
H.264 1080p 3 - 9 Mbps High Profile (Live)
H.264 720p 1.5 - 6 Mbps High Profile (Live)
H.264 480p 0.5 - 2.0 Mbps High Profile (Live)
H.264 360p 0.4 - 1.0 Mbps High Profile (Live)
H.264 240p 0.3 - 0.7 Mbps High Profile (Live)
H.264 1080p CBR 15 Mbps MAIN Profile
H.264 480p CBR 2.3 Mbps MAIN Profile
H.264 360p CBR MAIN Profile
H.264 432p CBR MAIN Profile
H.264 576p CBR MAIN Profile
H.264 720p CBR MAIN Profile
H.264 1080p CBR MAIN Profile
H.264 576p CBR - 3 Mbps MAIN Profile
H.264 720p CBR - 4 Mbps MAIN Profile
H.264 1080p CBR - 5Mbps MAIN Profile
H.264 15-30 Mbps MAIN Profile
H.264 L10 10 Mbps
H.264 WebRTC Baseline
H.265/HEVC LGOP 4:2:2
H.265/HEVC 10 Mbps LGOP
H.265/HEVC 25 Mbps LGOP
H.265/HEVC 50 Mbps LGOP
H.265/HEVC 100 Mbps LGOP
H.265/HEVC 4K 25 Mbps LGOP
H.265/HEVC 4K 50 Mbps LGOP
NDI HX H.264 - High Profile
NDI HX H.265 - High Profile
MPEG-5 EVC Baseline Profile
MPEG-5 EVC Main Profile
MPEG VVC/H266 Main Profile
ProRes 422 (SQ/HQ/LT)
ProRes 4444
ProRes 4444XQ
Google® VP6 / VP7 / VP8
Google® VP9 (Full HD)
Google® VP9 (4K)
Uncompressed UYVY 422 / V210 / RGBA
AOMedia Video 1 (Full HD)
AOMedia Video 1 (4K)

Proxy Formats

Output Proxy Formats

XAVC LGOP 25 / 35 Mbps
AVC Ultra (LGOP 6/12/25 Mbps)
H.264 @ 500 Kbps Flash
H.264 @ 486p 1 / 1.5 Mbps Flash
H.264 360p @ 1.6 Mbps Flash
H.264 720 480p @ 8 / 10 Mbps Flash
H.264 720p @ 8 / 15 / 16 / 20 / 24 / 25 Mbps Flash
H.264 854 480p @ 8 / 10 Mbps Flash
H.264 960 540p @ 3 Mbps Flash
H.264 1080p @ 8 / 15 / 16 / 20 / 24 / 25 Mbps Flash
H.264 SD @ 4 / 8 / 15 / 20 / 25 Mbps
H.264 480p @ 0.5 - 2 Mbps High Profile (Live)
H.264 360p @ 0.4 - 1 Mbps High Profile (Live)
H.264 240p @ 0.3 - 0.7 Mbps High Profile (Live)
ProRes Proxy 1920x1080
ProRes Proxy 1280x720
ProRes Proxy 960x540
ProRes Proxy SD (16:9 Raster)
ProRes Proxy SD
MPEG-1 (layer 2) @ 1.5 Mbps
Avid MPEG-2 (SIF @ 2Mbps)
H.264 MOG 1Mbps
H.264 Interplay Web (SD, 800 Kbps, and 2 Mbps)
Sony Proxy AV (MPEG-4 Part-2) @1.5 Mbps

OTT Formats *

Output OTT Formats

H.264 2160p 35 - 68 Mbps High Profile
H.264 1440p 16 - 24 Mbps High Profile
H.264 1080i 35 Mbps High Profile
H.264 1080p 8 - 12 Mbps High Profile
H.264 720p 5 - 7.5 Mbps High Profile
H.264 480p 2.5 - 4 Mbps High Profile
H.264 360p 1 - 1.5 Mbps High Profile
H.264 2160p 13 - 51 Mbps High Profile (Live)
H.264 1440p 6 - 18 Mbps High Profile (Live)
H.264 1080p 3 - 9 Mbps High Profile (Live)
H.264 720p 1.5 - 6 Mbps High Profile (Live)
H.264 480p 0.5 - 2.0 Mbps High Profile (Live)
H.264 360p 0.4 - 1.0 Mbps High Profile (Live)
H.264 240p 0.3 - 0.7 Mbps High Profile (Live)
H.264 360p CBR MAIN Profile
H.264 432p CBR MAIN Profile
H.264 576p CBR MAIN Profile
H.264 720p CBR MAIN Profile
H.264 1080p CBR MAIN Profile
H.264 576p CBR - 3 Mbps MAIN Profile
H.264 720p CBR - 4 Mbps MAIN Profile
H.264 1080p CBR - 5Mbps MAIN Profile
H.265/HEVC 10 Mbps LGOP
H.265/HEVC 25 Mbps LGOP
H.265/HEVC 50 Mbps LGOP
H.265/HEVC 100 Mbps LGOP
H.265/HEVC LGOP 4:2:2
Google® VP9 (Full HD)
Google® VP9 (4K)

* Optional output

Product Integrations

Editing Systems	MAM / PAM / DAM	Cameras	Consumer Cloud Storages
Adobe Premiere Pro	CatDV MAM	Canon (DSLR5D, DSLR 7D)	Dropbox
AVID Media Composer	CatDV PAM	Canon (DSLR C300, DSLR C100)	Google Drive
AVID Media Central UX	CatDV DAM	ARRI Alexa XT (ARRIRAW)	Microsoft One Drive
AVID Media Central Cloud UX	eMAM Media Asset Management	Panasonic AU-EVA1	Apple I Cloud Drive
Apple Final Cut Pro X	Telestream: Masstech	Panasonic GH5 Cameras	CDN's
Edius: Pro 8 and Workgroup 9 and 10	AVID Interplay	Panasonic CX350 HEVC	Lumen
BlackMagic: DaVinci Resolve Studio	AXLE MAM	Panasonic PTZ Cameras	Fastly
Autodesk: Flame	Editshare Flow	Ikegami Gfpack	Akamai Technologies
Storage	MOG Vizzi	JVC AVC HD camera models	Microsoft Azure
AVID Nexis Storage	Medialoopster MAM	LUMIX DC-S1H	Cloudflare
Avid Unity™ MediaNetwork	Professional Cloud Storages	NewTek PTZ3 UHD Camera	Limelight Networks
Dynamic Drive Pool SAN Storage	Adobe Creative Cloud	NewTek PTZ3 Camera	Amazon CloudFront
Facilis Terrablock	Amazon EC2	RED Digital Cinema	BootstrapCDN
Harmonic MediaGrid	Amazon S3	GOPRO	StackPath
Quantum: Storenext	Amazon S3 Glacier	Card Readers	KeyCDN
Scalelogic: NX2 & ZX NAS Storage	Microsoft Azure Storage	Panasonic P2 (AJ PCD 2 / AJ PCD 20/30/35)	Rackspace
Editshare EFS	Microsoft Azure Virtual Machines	Panasonic P2 (AJ MPD1)	Alibaba Cloud Content Delivery Service
EMC: Isilon	Tencent: Cloud Storage	Panasonic P2 (AU-XPD1E / AU-XPD3EJ)	CacheFly
QNAP	Lucidlink Cloud NAS	Panasonic P2 (AG HPG 20)	Verizon
Studio Network Solutions: EVO	Google Cloud Storage	Sony XDCAM EX (SxS Cards): SBAC-US10/20/30	Social Media *Optional
Oracle Storage	IBM Cloud Object Storage	Sony XDCAM EX (SxS Cards): SBAC-UT100	Facebook
Netapp	IBM Generic S3	Sony XDCAM EX (SxS Cards): MRW E-80	Twitch
Transfer Acceleration Protocols	Stream	Sony XDCAM EX (SxS Cards): MRW E-90	X (Twitter)
File Catalyst Direct	Newtek NDI	Sony Disc Reader: PDW-U1, PDW-U2	YouTube
IBM: Aspera File Transfer	Haivision SRT	Video Router Control Protocols	Vimeo
Peripheral Devices	Zixi	Videohub Ethernet Protocol	VTR Decks
Countour Shuttle Pro V2	Structures	Evertz > SONY HDS-X5800 - Evertz BRC controller (7700R-SC-BRC) (Quartz Protocol)	XDCAM HD: Disc (PDW 1500, PDW HD1500)
Elgato Stream Deck	XAVC Structures	Grass Valley > Trinix 5122 - CM4000 GrassValley Router Control (Jupiter ASCII protocol)	XDCAM HD: Disc (PDW F70)
Archive	Audio	Grass Valley > Sirius 840 - Router Control module 2464 (Probel SW-P-08 Protocol)	XDCAM Station (XDS1000)
Archware P5	Dante *Negotiated separately		

Server Options

Features		Specs	
System	Platform	Dell XR12	
	GPU	1x Nvidia A2	
	Video IO	1x DeckLink 8K Pro	
	Storage Drive	8TB SSD**	
	Operating System Drive	480GB RAID 1	
	Operating System	Windows 10 Enterprise (LTSC)	
Connectivity	Networking	10Gb Ethernet Port SFP28	2
		25Gb Ethernet Port SFP+	4
	Video	VGA Out	1
	USB	2.0	1
		3.0	1
	Serial		1
	BNC 12G In/Out		4
	Ref. In		1
Power Requirements		Dual 1400W	
Extended Connectivity	Peripheral Module**	LTC Input	1
		Audio Out	1
		Breakout Connector	1
	Breakout Cable**	RS422	4
		GPO branch with 4 outputs	1
		GPI branch with 4 inputs	1
Other	Dimensions & Weight		2RU, 463x482x86.8mm (D, W, H), ~20.5 kg
	Delivery Packaging		470x487x92mm (D, W, H), ~25Kg
	Temperature	Storage**	-40°C to 65°C (-40°F to 149°F)
		Continuous Operation	10°C to 35°C (50°F to 95°F)
	What is Included	Power Cable	2x C13 to C14
		Other	Static rails for 2/4-post racks

** Not included by default

Concurrent Media Operations

With mDECK Solid io, it is possible to run different media operations simultaneously, thus guaranteeing a universe of distinct arrangements to meet the challenging day-to-day activities of media production companies.

Media operations include recording, ingesting, transcoding, playback, and file preview.

mDECK Solid io supports up to 4 media operations at the same time. Within this margin, you can combine the operations shown in the table below:

Concurrent Media Operations			
Record	Ingest & Transcode	Playback	File Preview
Up to 4 live channels	Up to 1 operation	Up to 4 playback files	Up to 5 files preview

Note: when using operations dependent on video inputs and outputs, the physical limit of the video card must be respected. Thus, the sum of these operations cannot be greater than 4.

Product

Part Number	Product	Description
mdslio	mDECK Solid io	Deck appliance for hybrid workflows of up to 4 combined media operations

Available Options

Choose from the products below to customize the mDECK Solid io according to your business rules.

Production Tools

Tools for asset management and workflow orchestration.



mPAM

Benefit from a state-of-the-art content and production asset manager tool with mPAM. Streamline daily operations and empower your creative teams with the right tools to find, manage, track, enhance, and deliver media files throughout the entire production ecosystem from a single interface.



mPLAN

Set up scheduled events not only from the standard scheduler but through a unique rollout view interface. mPLAN is a tool that maintains a single rollout view of all scheduled events, allowing the management of the ingests process very efficiently. It manages multiple scheduled events across a variety of recording platforms in a multichannel environment using router control cross-points.

Part Number	Product	Description
mpam1usw	mPAM	Content and production asset manager per licensed user
mgslsb	mPLAN	Scheduler & Router Control per licensed channel

Note: Adding optional features might affect the number of simultaneous operations.

Add-ons

Output options to complement your workflows.

Part Number	Product	Description
cnnsmp	Social media	Simultaneous social media shares
cnnottop	OTT	Multiple OTT output resolutions

Note: Adding optional features might affect the number of simultaneous operations.

Artificial Intelligence

Artificial intelligence engine to boost and facilitate media tasks even more.

Default (already included)	
Black frames detection	Voice activity detection
Video freeze detection	Silence detection
Black margins detection	Loudness detection
Audio clipping detection	Loudness balance
Audio mute detection	Vehicle detection
Audio phase detection	License plate detection
Audio mono detection	Concept tagger
Timecode gap detection	Bouncing boxes
Scene change detection	Update existing interplay entry with new metadata
Transformation	
Frame rate conversion	Crop black margins
Remove audio clicks	AI upscale
Remove audio clipping	Blur license plates

Additional AI Operations	
Part Number	Product
aistop	Option to enable Speech-to-Text
aifrop	Option to enable Face Recognition
aiocop	Option to enable Optical Character Recognition
aiodop	Option to enable Object Detection

Note: Adding optional features might affect the number of simultaneous operations.

Hardware

Customize your solution to your day-to-day media needs.

Part Number	Product	Description
pcbx	Peripheral module	Optional MOG module to expand I/O available with 1x LTC, 1x audio output, 1x GPI, 1x GPO and 4x RS422

Note: Adding optional features might affect the number of simultaneous operations.

Storage

Option for local storage.

Part Number	Description
mdslssd8t	8TB of SSD storage

Contact our sales team at sales@mog-technologies.com to find out how to purchase or in case you need more information.

Disclaimer: the data and information contained in this document is representative and may be incomplete. If in doubt, please contact our sales team at sales@mog-technologies.com. The information contained in this document is not to be construed as a warranty, express or implied, including, but not limited to, a warranty of merchantability or fitness for a particular purpose. In no event will MOG be liable for any incidental or consequential damages resulting from the use, misuse, or inability to use the product. This exclusion applies regardless of whether such damages are sought on the basis of breach of warranty, breach of contract, negligence, strict liability in tort or any other legal theory. Contact our sales team at sales@mog-technologies.com to find out how to purchase or in case you need more information.